§ 32.58

source is such that the americium-241 will not be released or be removed from the source under normal conditions of use and handling of the source; and

(2) The source has been subjected to and has satisfactorily passed the prototype tests prescribed by §32.102, Schedule C, of this part.

[30 FR 8192, June 26, 1965, as amended at 43 FR 6923, Feb. 17, 1978]

§ 32.58 Same: Labeling of devices.

Each person licensed under §32.57 shall affix to each source, or storage container for the source, a label which shall contain sufficient information relative to safe use and storage of the source and shall include the following statement or a substantially similar statement which contains the information called for in the following statement: 1

The receipt, possession, use and transfer of this source, Model ____, Serial No. _____, are subject to a general license and the regulations of the United States Nuclear Regulatory Commission or of a State with which the Commission has entered into an agreement for the exercise of regulatory authority. Do not remove this label.

CAUTION—RADIOACTIVE MATERIAL— THIS SOURCE CONTAINS AMERICIUM— 241. DO NOT TOUCH RADIOACTIVE POR-TION OF THIS SOURCE.

Name of manufacturer or initial transferor)

(Sec. 161, as amended, Pub. L. 83–703, 68 Stat. 948 (42 U.S.C. 2201); sec. 201, as amended, Pub. L. 93–438, 88 Stat. 1243 (42 U.S.C. 5841))

[30 FR 8192, June 26, 1965, as amended at 40 FR 8786, Mar. 3, 1975; 43 FR 6923, Feb. 17, 1978]

§ 32.59 Same: Leak testing of each source.

Each person licensed under §32.57 shall perform a dry wipe test upon each source containing more than 0.1 microcurie of americium-241 prior to transferring the source to a general licensee under §31.8 of this chapter. This test shall be performed by wiping the entire radioactive surface of the source with a filter paper with the application of moderate finger pressure. The radioactivity on the paper shall be measured

by using radiation detection instrumentation capable of detecting 0.005 microcurie of americium-241. If any such test discloses more than 0.005 microcurie of radioactive material, the source shall be deemed to be leaking or losing americium-241 and shall not be transferred to a general licensee under §31.8 of this chapter.

[30 FR 8192, June 26, 1965]

§32.60 [Reserved]

§ 32.61 Ice detection devices containing strontium-90; requirements for license to manufacture or initially transfer.

An application for a specific license to manufacture or initially transfer ice detection devices containing strontium-90 for distribution to persons generally licensed under §31.10 of this chapter will be approved if:

- (a) The applicant satisfies the general requirements specified in §30.33 of this chapter:
- (b) The applicant submits sufficient information regarding each type of device pertinent to evaluation of the potential radiation exposure, including:
- (1) Chemical and physical form and maximum quantity of strontium-90 in the device:
- (2) Details of construction and design of the source of radiation and its shielding;
- (3) Radiation profile of a prototype device;
- (4) Procedures for and results of prototype testing of devices to demonstrate that the strontium-90 contained in each device will not be released or be removed from the device under the most severe conditions likely to be encountered in normal handling and use:
- (5) Details of quality control procedures to be followed in manufacture of the device;
- (6) Description of labeling to be affixed to the device;
- (7) Instructions for handling and installation of the device:
- (8) Any additional information, including experimental studies and tests, required by the Commission to facilitate a determination of the safety of the device:

¹Sources licensed under §32.57 prior to January 19, 1975 may bear labels authorized by the regulations in effect on January 1, 1975.